



REJUVENATOR

Solvent Based Restoration Blend

PRODUCT DESCRIPTION

Deco-Crete (DC) Rejuvenator is a potent solvent blend used to restore solvent based acrylic sealers that have started to soften, fade, peel, crack, delaminate, & deteriorate. It can clear up white spots or blushing due to moisture issues. Rejuvenator melts the existing solvent based acrylic sealer & helps restore the original appearance without adding more acrylic. This allows the sealer to wear off naturally over time without stripping the existing bulk of the coating. Use Deco-Crete Rejuvenator to easily avoid all the issues that come up with over sealed stamped concrete.

TECHNICAL INFO

+ Coverage Rate	_____	100–200 sq. ft.
+ Drying Time	_____	30 min.–2 hrs.
+ Re-Coat Time	_____	4–24 hrs.
+ Foot Traffic	_____	4–6 hrs.
+ Wheel Traffic	_____	24–48 hrs.
+ Application Temp	_____	40°F–85°F
+ Wet Appearance	_____	Clear
+ Dry Appearance	_____	Clear

RECOMMENDED APPLICATIONS

- + Existing improperly sealed concrete substrates
- + Primer for Reseals
- + Stamped or Colored Concrete
 - Patios
 - Walkways
 - Porches



QUICK FACTS

- + Bring the shine & color back!
- + Works with your sealer, not against it
- + Slow Drying
- + Revitalizes existing sealer without adding more acrylic
- + Fixes sealers affected by unexpected issues
- + Easy to spray



REJUVENATOR

Solvent Based Restoration Blend

INSTRUCTIONS FOR USE

SURFACE PREPARATION

Concrete surface must be clean, dry, & free of all contaminants. Do not apply DC Rejuvenator if rain is expected within 12hrs. Substrate temperature must be between 40°F–80°F. If applied outside these limits this product may not fix the original issue & potentially make a problem worse.

APPLICATION

Using a solvent resistant sprayer, apply DC Rejuvenator to surface at approximately 100–200 sq. ft. per gallon depending on porosity & texture of substrate to allow existing coating adequate time to re-emulsify. Immediately backroll with a solvent resistant 3/8"–3/4" nap roller. Applying DC Rejuvenator too thin may yield less than desirable results. If applying two coats, wait approximately 4–6 hrs. between coats. Allow DC Rejuvenator to dry for 24 hrs. for light traffic & at least 48 hrs. for heavy traffic. If sprayer application is not applicable, apply using a 3/8"–3/4" nap roller. For cases of extreme acrylic buildup, contact your local Deco-Crete Distributor for additional instructions.

PRECAUTIONS

- + DC Rejuvenator will not freeze during storage, however, allow temperature to rise to or above 50°F prior to application.
- + Keep away from open flames. DC Rejuvenator is flammable & is very susceptible to ignition.
- + Apply DC Rejuvenator to solvent based acrylic sealers only.

It is always recommended to test the product in a small, inconspicuous area for desired results prior to application. Coverage rates may vary for all coatings & substrates depending on porosity, density, texture, etc.

SHELF LIFE, PACKAGING, & CLEAN-UP

- + Two year shelf life in it's original, sealed, unopened container
- + Packaged in 1 gal. jugs, 5 gal. pails, & 55 gal. drums
- + Use Xylene to clean & dispose of containers in accordance with local & federal regulations



For tutorials & even more decorative concrete content,
follow the QR code here or find us on social media.



www.eco-cretesupply.com